

BACTERIA CARRIER MATERIAL

Product properties

- large usable surface
- high efficiency
- low abrasion of adherent bacteria due to the stream
- easy cleaning and simple handling
- resistant and pH-neutral
- high chemical resistance




TECHNICAL DATA

Material	special HDPE
Diameter	20 oder 55 mm
specific Surface	500 m ² /m ³
Bulk density	200 g/l
Material density	0.95 kg/l
Max. Temperature	80 °C

All data are approximate data!

- suitable for aerobic and anaerobic processes
- COD - reduction
- BOD - reduction
- nitrification
- recirculation by stream




FUNCTION

In waste water treatment microorganism are of particular importance because they are able to degrade pollutants. In conventional aeration tanks these organism appear in small flocules dispersed in the water. This is called activated sludge.

By the proportion of the activated sludge in the aeration basin, the degradation rate can be controlled. But the amount of the activated sludge in the tank cannot be increased arbitrarily. At a certain amount of suspended biomass the waste water will become too viscous/muddy for an effective treatment. In this case the tank volume has to be increased by civil works to keep the

higher amount of activated sludge in suspension. As an alternative to complex and cost intensive civil works respectively new buildings, it is possible to increase artificial the biomass in the tank by the application of biofilm carriers. Depending on the tank size, its form and internals the amount of activated sludge can be doubled. Newpond® is a biofilm carrier with a very high specific surface. It meets all demands on a modern high efficiently biofilm carrier. Microorganism grow best in so-called biofilms. These slimy films adhere everywhere where the microorganism find a surface they can attach to. On the carrier a biofilm develops which is made up of several layers. The living conditions within these layers are partly quite different. By this means a plenty of pollutants can be degraded.



NEWPOND® IS APPLICABLE FOR ALL COMMON PROCESSES USING BIOFILM TECHNOLOGY

- for rotating drum systems
- for fluidized bed reactor systems
- for sewage treatment plants
- for fixed-bed reactor systems like trickling filter
- for the expansion of existing treatment plants

Our continuing commitment to quality product, may mean a change without notice of specification, design and other content included in this brochure.





Since 1983 your partner for wastewater treatment products.
Proudly Made in Italy.



CONTACT

Geotek-Tierre S.R.L.

Phone +39 035 810296

TeleFax + 39 035 810296

email: info@geotierre.com

Via Prato Pieve 54, 24060 Casazza (BG) - ITALY

Certified ISO9001:2015

Geotek-Tierre SRL
Via Prato Pieve 54
24060 Casazza (BG)
Italy



Azienda con sistema
di gestione qualità
certificato secondo la
Norma ISO9001:2015

geotierre.com